

# **COMSATS University Islamabad, Lahore Campus**

Defence Road, Off Raiwind Road, Lahore

Tender No. CUI-LHR-TN-21-1493 Case # 3383

# **Single Stage Two Envelop Procedure**

### Title of Tender: Product Stability Chamber for Dr. Muhammad Yar, Department of IRCBM

## A. GENERAL TERMS AND CONDITIONS

- 1. All pages of bidding documents are mandatory to be signed / stamped, meaning thereby bidder agrees to our terms & conditions mentioned herein, failing which the bid may be rejected.
- 2. Any addition, deletion or modification of any clause of the procurement terms & conditions/ BoQs of CUI Lahore Campus by any vendor will not be acceptable and may lead to rejection of the bid.
- 3. Only registered Suppliers, who are on Active Taxpayers List (ATL) of FBR (GST & Income Tax), are eligible to participate in tender.
- 4. The contract will be executed and handed over in satisfactory conditions up to the entire satisfaction of COMSATS University Islamabad, Lahore Campus.
- 5. Documents along with Pay Order / Demand Draft amounting to <u>Rs. 500/-</u> as a tender document fee (Non-Refundable) shall be submitted in favor of COMSATS University Islamabad, Lahore Campus to the address given below. No bid will be accepted without tender documents' fee.
- 6. Part / Advance payments is not allowed.
- 7. <u>The exact completion/installation/ delivery time from the date of the purchase / work order will be</u> 60 days. The handing over / completion time for this contract is of critical importance.
- 8. Your bid proposal should be inclusive of freight and all other taxes and to be delivered at COMSATS University Islamabad (CUI), Lahore Campus's premises.
- 9. After opening of bids, CUI-Lahore Campus will examine the bids for completeness as per tender document.
- 10. In case more than one bidder have quoted same rates for an item; the bidder securing more items (in terms of cost) will be awarded the specific item.
- 11. Purchase order (s) will be awarded to the evaluated lowest or technically recommended bidder (s) on the basis of item wise / subtotal wise / grand total wise according to the nature of BoQs.
- 12. The bid should be submitted in a sealed envelope up to <u>August 25, 2021</u> on or before <u>1400hrs</u> and will be opened on the same date <u>at 1430hrs</u> in the presence of available bidders. In case of any holiday is announced by the Govt. OR any unforeseeable circumstances that prevent the tender from being opened on the date announced (Force Majure Situation), the tenders will be opened on the very next working day. Timing will remain as mentioned in the tender notice.
- 13. COMSATS University Islamabad, Lahore Campus, will follow the PPRA rule of <u>Single Stage Two</u> <u>Envelope Procedure:</u>
  - i. The bid shall comprise a single package containing <u>two separate envelopes</u>. Each envelope shall contain separately the <u>financial proposal</u> and the <u>technical proposal</u>;

#### Signature & Stamp of Bidder

- ii. The envelopes shall be marked as "FINANCIAL PROPOSAL" and "TECHNICAL PROPOSAL" in bold and legible letters to avoid confusion;
- iii. Initially, only the envelope marked <u>"TECHNICAL PROPOSAL"</u> shall be opened;
- iv. The envelope marked as <u>"FINANCIAL PROPOSAL</u>" shall be retained in the custody of the procuring agency without being opened;
- v. The procuring agency shall evaluate the technical proposal in a manner prescribed in advance, without reference to the price and reject any proposal which does not conform to the specified requirements;
- vi. During the technical evaluation no **amendments** in the technical proposal shall be permitted;
- vii. The financial proposals of bids shall be opened publicly at a time, date and venue announced and communicated to the bidders in advance;
- viii. After the evaluation and approval of the technical proposal the procuring agency, shall at a time within the bid validity period, publicly open the financial proposals of the technically accepted bids only. The financial proposal of bids found technically nonresponsive shall be returned un-opened to the respective bidders;
- ix. and
- x. The bid found to be the lowest evaluated bid shall be accepted.
- 14. The envelope should be marked as under;

Secretary, Purchase Committee COMSATS University Islamabad, Lahore Campus Defence Road, Off Raiwind Road, Lahore. Tel: 042-111-001-007, Ext: 875

#### 15. The envelope shall also bear the word "CONFIDENTIAL" and following identification quotation of <u>"Product Stability Chamber for Dr. Muhammad Yar, Department of IRCBM".</u>

- 16. The bid form (BoQs) must be duly filled in, stamped and signed by the authorized representative of the bidder.
- 17. If the vendor fails to deliver the goods / services to COMSATS University Islamabad (CUI), Lahore Campus within the given deadline, any of the following can be opted by CUI Lahore campus on the recommendation of the end user and approval of the authority;
  - a. An extension in the delivery period may be granted in case a valid reason/justification with necessary documentary evidence is provided by the vendor supporting the reason for delay.
  - b. A penalty upto 10% of the invoice value may be charged.
  - c. Purchase order may be cancelled along with confiscation of earnest money if the vendor fails to deliver the goods / services after the initial or extended delivery time, as the case may be.
- 18. If the delivered goods / services are not according to the required quality standards / specifications, the same shall be liable to be rejected after inspection. The vendor would be required to supply as per requirements mentioned in our BoQs, otherwise the purchase / work order will be cancelled after due date with confiscation of earnest money.
- 19. Any defective / sub-standard item (s) will be replaced by the bidder in same quoted cost. In case of failure to supply the specific item, CUI-Lahore may issue PO to next lowest bidder to supply the item while the difference of amount will be deducted from the 1st lowest bidder's earnest money.

#### Signature & Stamp of Bidder

- 20. Deduction of Income Tax and any other tax will be deducted at source according to Government prevailing rules.
- 21. Payment will be made on submission of Invoice in the name of "COMSATS University Islamabad (CUI), Lahore Campus" with a copy of delivery challan (s) after the complete order has been supplied, inspected and accepted which includes delivery / installation, and COMSATS acceptance / inspection thereof.
- 22. All prices should be valid for at least <u>90 days.</u> Withdrawal or any modification of the original offer within the validity period shall entitle CUI-Lahore Campus to forfeit the earnest money in favor of the CUI-Lahore Campus and / or put a ban on such vendor participation in tenders / works.
- 23. It is the sole responsibility of the agent / supplier / manufacturer to comply with the applicable laws, be national or international.
- 24. In case of any dispute or grievance, the matter shall be addressed as per PPRA rules.
- 25. The CUI-Lahore Campus reserves the right to modify the quantities of goods / services at any time before the award of purchase / work order.
- 26. Any defective / sub-standard item (s) will be replaced by the bidder in same quoted cost. In case of failure to supply the specific item, CUI-Lahore may issue PO to next lowest bidder to supply the item while the difference of amount will be deducted from the 1st lowest bidder's earnest money.
- 27. CUI-Lahore Campus shall disqualify any firm(s), if at any stage; it finds that the information submitted, or documents provided are inaccurate, fake, ambiguous or incomplete.
- 28. <u>05%</u> of the total value of the <u>Invoice</u> will be retained as security by COMSATS University Islamabad (CUI), Lahore Campus, and will be released after warranty period i.e. <u>(01 Year)</u> which will be counted from the date of Installation / Completion of work / Supply.
- 29. The bidder is required to furnish in form of <u>Bank deposit/ CDR / Pay order equivalent to 2% of the total Bid price as Earnest Money crossed in favor of "COMSATS University Islamabad, Lahore Campus"</u>. Which shall be released after the completion of work / supply on submission of written request on firm / company letterhead. Any bid not accompanied by Earnest Money shall be rejected without any right of appeal.
- 30. COMSATS University Islamabad, Lahore Campus reserves the rights to accept or reject the bid if;
  - i. Received without earnest money
  - ii. Received later than the date and time fixed for tender submission
  - iii. The tender is unsigned/ unstamped
  - iv. The offer is ambiguous
  - v. The offer is conditional
  - vi. The offer is from a firm, which is black listed by any Govt. Office.
  - vii. The offer is received by telephone/telex/fax/telegram.
  - viii. Any unsigned / ambiguous erasing, cutting / overwriting etc. is made.
- 31. The bidder should furnish a certificate as worded below in token of acceptance of all the terms and conditions of the tender otherwise the tender will not be considered under any circumstances.
- 32. The undersigned affirm that the terms and conditions as contained in this document have been read and accepted and that in the event of selection of my/our rate the agreement in the prescribed form will be entered into:

- <u>Company / Vendor Name:</u>.....
- <u>Postal Address:</u>.....

- <u>Signature:</u> .....
- Please also attach the Certificate supporting being Active Taxpayer as per requirement of <u>FBR.</u>

#### B. BoQs of Product Stability Chamber for Dr. Muhammad Yar, Department of IRCBM

# <u>Technical Portion (Please mention the quoted model/ brand in technical portion with no mention of price otherwise the bid will be rejected)</u>

allo mod	change in the wed. Any add lel / brand or ction of bid (f	Please mention the Quoted Model / Brand with meeting the all specifications			
Sr. #	Item Name	Specifications	C	Qty	mentioned in BoQs
1	Product Stability Chamber	MEDICINE STABLITY TEST CHAMBER with Computer MEDICINE STABLITY TEST CHAMBER Specifications: Display type: LCD Capacity: 500 L or more Temp. Range: -20 or lower~65°C or higher Humidity Control Range: 40 or lower~95% RH Shelves: 2 pcs adjustable Timing Range: 1~99 hour Refrigeration System: refrigerant CFC- free Alarm: High or low temperature/humidity, sensor & system failure Power Supply AC220V Chamber Size: (W×D×H) 700×800×900mm or bigger	01	No	

	· · · · · · · · · · · · · · · · · · ·	 CUI-I	LHR-PUR-Tender-001	
	<b>Computer Specifications</b>			
	27 Inch or bigger LED Display Screen			
	Size & Weight:			
	Height: 19.35inches (49.1 cm) or bigger			
	Width: 25.7 inches (65.0 cm) or bigger			
	Depth: 8.15 inches (20.7 cm) or bigger			
	System Requirements: Mac with Mini DisplayPort			
	connector or equivalent			
	Mac OS X v10.6.4 or later or equivalent			
	Display:			
	27-inch or bigger (diagonal viewable image size) thin			
	film transistor (TFT) active-matrix liquid crystal			
	display with in-plane switching (IPS).			
	Supported resolutions : 2560 by 1440 pixels, 1920 by			
	1080 pixels, 1280 by 720 pixels			
	Colors (maximum) : 16.7 million			
	Aspect ratio : 16:9			
	Viewing angle : 178° horizontal; 178° vertical			
	Brightness (typical) : 375 cd/m 2			
	Contrast ratio (typical) : 1000:1			
	Response time (typical) : 12 ms			
	Audio & Video:			
	Camera and microphone:			
	Built-in insight with microphone			
	Speakers: Built-in 2.1			
	speaker system (49 watts maximum)			
	Mini DisplayPort connector with audio support			
	Environmental Status Report:			
	Environmental Status Report.			
	• Arsenic-free display glass			
	<ul> <li>BFR-free</li> </ul>			
	• PVC-free 3			
	• Highly recyclable aluminum and glass			
	enclosures			
	• Mercury-free LED-backlit display			
	Periherals & Cables:			
	free self-powered USB 2.0 ports			
	Security slot			
	One cable with three connectors: Mini Display Port			
	with audio support, USB 2.0			
	AC power cord			
	Electrical & Operating Requirements:			
	Input voltage: 100V to 240V AC; 50-60Hz			
	Including installation and commissioning			
	One Year Local Warranty			
I				

# C. Bid Evaluation Criteria

All bids shall be evaluated in accordance with the following evaluation criteria and other terms & conditions set forth in this bidding document.

- 1. The bids shall be evaluated to strictly ensure that the quoted brand/ model meet all the BoQ/ specification requirements given in the bidding document for each item.
- 2. In addition to the BoQ requirements, vendors must meet the vendor qualification criteria /company profile requirements (if any), as set forth in this tender document.
- 3. Supporting literature (where available / required) of the quoted brand/ model must be attached for verification & technical evaluation of the required specification by the technical committee. In case of any clash is found between the quoted model and the supported literature may lead to rejection of bid.

## D. <u>Financial Portion (Price and Brand/Model to be mention only in Financial</u> Proposal in a separate sealed envelope) Strictly on our BoQs Form.

Vendors are required to provide both unit and total price of each item and calculations must be made carefully to avoid mistakes. However, in case, total price does not match with the unit price and quantity due to calculation error or typo error, any of the following can be opted

- 1. The bid may be rejected on the reason of ambiguity (OR
- 2. Unit price will be considered as final and total price of the respective item will be calculated by multiplying it with the quantity required. Sub-totals and grand total will also be corrected accordingly.

multiplying it with the quantity required. Sub-totals and grand total will also be corrected accordingly.								
No change in the BoQs (Specs & Qty.) of CUI-Lahore Campus, as detailed below, is allowed. Any additional information may be mentioned in the blank columns (i.e. model / brand or Price). Any modification in CUI-Lahore Campus BoQ may lead to rejection of bid (fully or partially).				Prices should be quoted inclusive of all applicable taxes				
Sr. #	Item Name	Specifications			Quoted Model / Brand	Unit Price (Rs.)	Total Amount (Rs.)	
1	Product Stability Chamber	MEDICINE STABLITY TEST CHAMBER with Computer MEDICINE STABLITY TEST CHAMBER Specifications: Display type: LCD Capacity: 500 L or more Temp. Range: -20 or lower~65°C or higher Humidity Control Range: 40 or lower~95% RH Shelves: 2 pcs adjustable	01	No				

		Temp. Range:				
	Product	-20 or lower~65°C or higher				
1	Stability	Humidity Control Range: 40 or lower~95%	01	No		
	Chamber	RH				
		Shelves: 2 pcs adjustable				
		Timing Range: 1~99 hour				
		Refrigeration System: refrigerant CFC- free				
		Alarm: High or low temperature/humidity				
		,sensor & system failure				
		Power Supply AC220V				
		Chamber Size: (W×D×H) 700×800×900mm				
		or bigger				

Computer Specifications         27 Inch or bigger LED Display Screen         Size & Weight:         Height:       19.35inches (49.1 cm) or bigger         Width:       25.7 inches (50.0 cm) or bigger         Depth:       8.15 inches (20.7 cm) or bigger         Dystm Requirements:       Mac with Mini         DisplayPort connector or equivalent       Mac OS X v10.6.4 or later or equivalent         DisplayPort connector or equivalent       Display:         27-inch or bigger (diagonal viewable       image size) thin film transistor (TFT)         active-matrix liquid crystal display with       in-plane switching (IPS).         Supported resolutions : 2560 by 1440       pixels, 1920 by 1080 pixels, 1280 by 720         pixels       Colors (maximum) : 16.7 million         Aspect ratio:       16.9         Viewing angle : 178° horizontal; 178°         vertical       Wrice:         Contrast ratio (typical) : 375 cd/m 2         Contrast ratio (typical) : 1000:1         Response time (Vipical) : 12 ms         Audio & Video:         Camera and microphone:         Built-in insight with microphone         Speakers: Built-in 2.1         speakers: Built-in 2.1         speakers: Built-in 2.1         speakers: Built-in 2.1         s		 CUI-L	HR-PUR-Tend	ler-001
Size & Weight: Height: 19.35 inches (49.1 cm) or bigger Width: 25.7 inches (6.0. cm) or bigger Depth: 8.15 inches (20.7 cm) or bigger System Requirements: Mac with Mini DisplayPort connector or equivalent Mac OS X v10.6.4 or later or equivalent Display: 27-inch or bigger (diagonal viewable image size) thin film transistor (TFT) active-matrix liquid crystal display with in-plane switching (IPS). Supported resolutions : 2560 by 1440 pixels, 1920 by 1080 pixels, 1280 by 720 pixels Colors (maximum) : 16.7 million Aspect ratio : 16:9 Viewing angle: 178° horizontal; 178° vertical Brightness (typical) : 375 cd/m 2 Contrast ratio (typical) : 1000:1 Response time (typical) : 12 ms Audio & Video: Camera and microphone: Built-in insight with microphone Speakers: Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: Arsenie-free display glass BFR-free PVC-free 3 Highly recyclable aluminum and glass enclosures Mercury-free LED-backlit display Peritherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini DisplayPort with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	Computer Specifications			
Size & Weight: Height: 19.35 inches (49.1 cm) or bigger Width: 25.7 inches (6.0. cm) or bigger Depth: 8.15 inches (20.7 cm) or bigger System Requirements: Mac with Mini DisplayPort connector or equivalent Mac OS X v10.6.4 or later or equivalent Display: 27-inch or bigger (diagonal viewable image size) thin film transistor (TFT) active-matrix liquid crystal display with in-plane switching (IPS). Supported resolutions : 2560 by 1440 pixels, 1920 by 1080 pixels, 1280 by 720 pixels Colors (maximum) : 16.7 million Aspect ratio : 16:9 Viewing angle: 178° horizontal; 178° vertical Brightness (typical) : 375 cd/m 2 Contrast ratio (typical) : 1000:1 Response time (typical) : 12 ms Audio & Video: Camera and microphone: Built-in insight with microphone Speakers: Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: Arsenie-free display glass BFR-free PVC-free 3 Highly recyclable aluminum and glass enclosures Mercury-free LED-backlit display Peritherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini DisplayPort with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	27 Inch or bigger LED Display Screen			
Height: 19.3 Sinches (49.1 cm) or bigger Widh: 25.7 inches (65.0 cm) or bigger Depht: 8.15 inches (20.7 cm) or bigger System Requirements: Mae with Mini DisplayPort connector or equivalent Mae OS X v10.6.4 or later or equivalent Display: 27-inch or bigger (diagonal viewable image size) thin film transistor (TFT) active-matrix liquid crystal display with in-plane switching (IPS). Supported resolutions : 2560 by 1440 pixels, 1920 by 1080 pixels, 1280 by 720 pixels Colors (maximum) : 16.7 million Aspect ratio : 16:9 Viewing angle: : 178° horizontal; 178° vertical Brightness (typical) : 375 cd/m 2 Contrast ratio (typical) : 1000:1 Response time (typical) : 12 ms Audio & Video: Camera and microphone: Built-in insight with microphone Speakers: Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: • Arsenic-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini DisplayPort with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning				
Widh: 25.7 inches (65.0 cm) or bigger Depth: 8.15 inches (20.7 cm) or bigger System Requirements: Max with Mini DisplayPort connector or equivalent Mac OS X v10.6.4 or later or equivalent Display: 27-inch or bigger (diagonal viewable image size) thin film transitor (TFT) active-matrix liquid crystal display with in-plane switching (IPS). Supported resolutions : 2560 by 1440 pixels, 1920 by 1080 pixels, 1280 by 720 pixels Colors (maximum) : 16.7 million Aspect ratio : 16:9 Viewing angle : 178° horizontal; 178° vertical Brightness (typical) : 375 cd/m 2 Contrast ratio (typical) : 12 ms Audio & Video: Camera and microphone: Built-in insight with microphone Speakers; Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report:• Arsenic-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	e			
Depth: 8.15 inches (20.7 cm) or bigger System Requirements: Max with Mini DisplayPort connector or equivalent Mac OS X v10.6.4 or later or equivalent Display: 27-inch or bigger (diagonal viewable image size) thin film transistor (TFT) active-matrix liquid crystal display with in-plane switching (IPS). Supported resolutions : 2560 by 1440 pixels, 1920 by 1080 pixels, 1280 by 720 pixels Colors (maximum) : 16.7 million Aspect ratio : 16:9 Viewing angle : 178° horizontal; 178° vertical Brightness (typical) : 375 cd/m 2 Contrast ratio (typical) : 1000:1 Response time (typical) : 12 ms Audio & Video: Camera and microphone: Built-in insight with microphone Speakers: Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: Arsenic-free display glass BFR-free PVC-free 3 Highly recyclable aluminum and glass enclosures Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini DisplayPort with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning				
System Requirements: Mac with Mini DisplayPort connector or equivalent Mac OS X V10.64 or later or equivalent Display: 27-inch or bigger (diagonal viewable image size) thin film transistor (TFT) active-matrix liquid crystal display with in-plane switching (IPS). Supported resolutions : 2560 by 1440 pixels, 1920 by 1080 pixels, 1280 by 720 pixels Colors (maximum) : 16.7 million Aspect ratio : 16:9 Viewing angle : 178° horizontal; 178° vertical Brightness (typical) : 375 cd/m 2 Contrast ratio (typical) : 1000:1 Response time (typical) : 12 ms Audio & Video: Camera and microphone Built-in insight with microphone Speakers: Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: • Arsenie-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltags: 100V to 240V AC; 50- 60Hz Including installation and commissioning				
DisplayPort connector or equivalent Mac OS X v10.6.4 or later or equivalent Display: 27-inch or bigger (diagonal viewable image size) thin film transistor (TFT) active-matrix liquid crystal display with in-plane switching (IPS). Supported resolutions : 2560 by 1440 pixels, 1920 by 1080 pixels, 1280 by 720 pixels Colors (maximum) : 16.7 million Aspect ratio : 16:9 Viewing angle : 178° horizontal; 178° vertical Brightness (typical) : 375 cd/m 2 Contrast ratio (typical) : 1000:1 Response time (typical) : 1000:1 Response time (typical) : 12 ms Audio & Video: Camera and microphone: Built-in insight with microphone Speakers: Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: • Arsenic-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powerd USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	1			
Mac OS X v10.6.4 or later or equivalent         Display:         27-inch or bigger (diagonal viewable         image size) thin film transistor (TFT)         active-matrix liquid crystal display with         in-plane switching (IPS).         Supported resolutions : 2560 by 1440         pixels.         Colors (maximum) : 16.7 million         Aspect ratio : 16:9         Viewing angle : 178° horizontal; 178°         vertical         Brightness (typical) : 375 cd/m 2         Contrast ratio (typical) : 12 ms         Audio & Video:         Camera and microphone:         Built-in insight with microphone         Speakers: Buil-in 2.1         speaker system (49 watts maximum)         Min DisplayPort connector with audio         support         Environmental Status Report:         • Arsenic-free display glass         • BFR-free         • PVC-free 3         • Highly recyclable aluminum         and glass enclosures         • Mercury-free LED-backlit display         Periherals & Cables:         free self-powered USB 2.0 ports         Security slot         One cable with three connectors: Mini         Display Port with audio support, USB 2.0         AC p				
Display:         27-inch or bigger (diagonal viewable image size) thin film transistor (TFT) active-matrix liquid crystal display with in-plane switching (IPS).         Supported resolutions : 2560 by 1440 pixels, 1920 by 1080 pixels, 1280 by 720 pixels         Colors (maximum) : 16.7 million Aspect ratio : 16.9         Viewing angle : 178° horizontal; 178° vertical         Brightness (typical) : 375 cd/m 2         Contrast ratio (typical) : 1000:1         Response time (typical) : 12 ms Audio & Video:         Camera and microphone:         Built-in insight with microphone         Spcakers; Built-in 2.1         spcaker system (49 watts maximum)         Mini DisplayPort connector with audio support         Environmental Status Report:         • Arsenic-free display glass         BFR-free         • PVC-free 3         • Highly recyclable aluminum and glass enclosures         • Mercury-free LED-backlit display         Periherals & Cables:         free self-powered USB 2.0 ports         Security slot         One cable with three connectors: Mini         Display Port with audio support, USB 2.0 AC power cord         Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz         Including installation and commissioning				
27-inch or bigger (diagonal viewable image size) thin film transistor (TFT) active-matrix liquid crystal display with in-plane switching (IPS).         Supported resolutions : 2560 by 1440 pixels, 1920 by 1080 pixels, 1280 by 720 pixels         Colors (maximum) : 16.7 million Aspect ratio : 16:9         Viewing angle : 178° horizontal; 178° vertical         Brightness (typical) : 375 cd/m 2         Contrast ratio (typical) : 1000:1         Response time (typical) : 1000:1         Response time (typical) : 12 ms Audio & Video:         Camera and microphone:         Built-in insight with microphone Speakers: Built-in 2.1         speaker system (49 watts maximum) Mini DisplayPort connector with audio support         Environmental Status Report:         • Arsenic-free display glass         • BFR-free         • PVC-free 3         • Migulty recyclable aluminum and glass enclosures         • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot         One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	1			
image size) thin film transistor (TFT) active-matrix liquid crystal display with in-plane switching (IPS). Supported resolutions : 2560 by 1440 pixels, 1920 by 1080 pixels, 1280 by 720 pixels Colors (maximum) : 16.7 million Aspect ratio : 16:9 Viewing angle : 178° horizontal; 178° vertical Brightness (typical) : 375 cd/m 2 Contrast ratio (typical) : 1000:1 Response time (typical) : 12 ms Audio & Video: Camera and microphone: Built-in insight with microphone Spcakers: Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: • Arsenic-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Sccurity slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning				
active-matrix liquid crystal display with in-plane switching (JPS).         Supported resolutions : 2560 by 1440 pixels         pixels         Colors (maximum) : 16.7 million Aspect ratio : 16:9         Viewing angle : 178° horizontal; 178° vertical         Brightness (typical) : 375 cd/m 2         Contrast ratio (typical) : 1000:1         Response time (typical) : 12 ms Audio & Video:         Camera and microphone:         Built-in insight with microphone         Speakers: Built-in 2.1         speaker system (49 watts maximum)         Mini DisplayPort connector with audio support         environmental Status Report:         Arsenic-free display glass         BFR-free         PVC-free 3         Highly recyclable aluminum and glass enclosures         Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot         One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz         Including installation and commissioning				
in-plane switching (IPS). Supported resolutions : 2560 by 1440 pixels, 1920 by 1080 pixels, 1280 by 720 pixels Colors (maximum) : 16.7 million Aspect ratio : 16.9 Viewing angle : 178° horizontal; 178° vertical Brightness (typical) : 375 cd/m 2 Contrast ratio (typical) : 1000:1 Response time (typical) : 10 ms Audio & Video: Camera and microphone: Built-in insight with microphone Speakers: Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: Arsenic-free display glass BFR-free PVC-free 3 Highly recyclable aluminum and glass enclosures Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	- · · · · · · · · · · · · · · · · · · ·			
Supported resolutions : 2560 by 1440         pixels         Colors (maximum) : 16.7 million         Aspect ratio : 16:9         Viewing angle : 178° horizontal; 178°         vertical         Brightness (typical) : 375 cd/m 2         Contrast ratio (typical) : 1000:1         Response time (typical) : 12 ms         Audio & Video:         Camera and microphone:         Built-in insight with microphone         Speakers: Built-in 2.1         speakers: System (49 watts maximum)         Mini DisplayPort connector with audio         support         Environmental Status Report:         •         •         PVC-free 3         •         •         PVC-free 3         •         •         Nercury-free LED-backlit display         Periherals & Cables:         free self-powered USB 2.0 ports         Security slot         One cable with three connectors: Mini         Display Port with audio support, USB 2.0         AC power cord         Electrical & Operating Requirements:         Input voltage: 100V to 240V AC; 50-60Hz         Including installation and commissioning				
pixels, 1920 by 1080 pixels, 1280 by 720 pixels Colors (maximum) : 16.7 million Aspect ratio : 16:9 Viewing angle : 178° horizontal; 178° vertical Brightness (typical) : 375 cd/m 2 Contrast ratio (typical) : 1000:1 Response time (typical) : 12 ms Audio & Video: Camera and microphone: Built-in insight with microphone Speakers: Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: • Arsenic-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	1 0 0 0			
Colors (maximum) : 16.7 million         Aspect ratio : 16:9         Viewing angle : 178° horizontal; 178°         vertical         Brightness (typical) : 375 cd/m 2         Contrast ratio (typical) : 1000:1         Response time (typical) : 1000:1         Response time (typical) : 12 ms         Audio & Video:         Camera and microphone:         Built-in insight with microphone         Speakers: Built-in 2.1         speaker system (49 watts maximum)         Mini DisplayPort connector with audio         support         Environmental Status Report:         •       Arsenic-free display glass         •       BFR-free         •       PVC-free 3         •       Highly recyclable aluminum and glass enclosures         •       Mercury-free LED-backlit display         Periherals & Cables:       free self-powered USB 2.0 ports         Security slot       One cable with three connectors: Mini         Display Port with audio support, USB 2.0       AC power cord         Electrical & Operating Requirements:       Input voltage: 100V to 240V AC; 50-60Hz         Including installation and commissioning       Including installation and commissioning	•••			
Aspect ratio : 16:9         Viewing angle : 178° horizontal; 178°         vertical         Brightness (typical) : 375 cd/m 2         Contrast ratio (typical) : 1000:1         Response time (typical) : 12 ms         Audio & Video:         Camera and microphone:         Built-in insight with microphone         Speakers: Built-in 2.1         speaker system (49 watts maximum)         Mini DisplayPort connector with audio         support         Environmental Status Report:         •         •         Arsenic-free display glass         •         •         PVC-free 3         •         •         Mercury-free LED-backlit display         Periherals & Cables:         free self-powered USB 2.0 ports         Security slot         One cable with three connectors: Mini         Display Port with audio support, USB 2.0         AC power cord         Electrical & Operating Requirements:         Input voltage: 100V to 240V AC; 50-60Hz         Including installation and commissioning	pixels			
Viewing angle : 178° horizontal; 178° vertical Brightness (typical) : 375 cd/m 2 Contrast ratio (typical) : 1000:1 Response time (typical) : 12 ms Audio & Video: Camera and microphone: Built-in insight with microphone Speakers: Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: • Arsenic-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- GOHz Including installation and commissioning	Colors (maximum) : 16.7 million			
vertical Brightness (typical) : 375 cd/m 2 Contrast ratio (typical) : 1000:1 Response time (typical) : 12 ms Audio & Video: Camera and microphone: Built-in insight with microphone Speakers: Built-in 2.1 spcaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: • Arsenic-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	Aspect ratio : 16:9			
Brightness (typical) : 375 cd/m 2         Contrast ratio (typical) : 1000:1         Response time (typical) : 12 ms         Audio & Video:         Camera and microphone:         Built-in insight with microphone         Speakers: Built-in 2.1         speaker system (49 watts maximum)         Min DisplayPort connector with audio         support         Environmental Status Report:         •       Arsenic-free display glass         •       BFR-free         •       PVC-free 3         •       Highly recyclable aluminum and glass enclosures         •       Mercury-free LED-backlit display         Periherals & Cables:       free self-powered USB 2.0 ports         Security slot       One cable with three connectors: Mini         Display Port with audio support, USB 2.0       AC power cord         Electrical & Operating Requirements:       Input voltage: 100V to 240V AC; 50-         60Hz       Including installation and commissioning	Viewing angle : 178° horizontal; 178°			
Contrast ratio (typical) : 1000:1 Response time (typical) : 12 ms Audio & Video: Camera and microphone: Built-in insight with microphone Speakers: Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: • Arsenic-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning				
Response time (typical) : 12 ms         Audio & Video:         Camera and microphone:         Built-in insight with microphone         Speakers: Built-in 2.1         speaker system (49 watts maximum)         Mini DisplayPort connector with audio         support         Environmental Status Report:         •         •         Arsenic-free display glass         •         BFR-free         •         •         Nercury-free 2         •				
Audio & Video:         Camera and microphone:         Built-in insight with microphone         Speakers: Built-in 2.1         speaker system (49 watts maximum)         Mini DisplayPort connector with audio         support         Environmental Status Report:         • Arsenic-free display glass         • BFR-free         • PVC-free 3         • Highly recyclable aluminum         and glass enclosures         • Mercury-free LED-backlit display         Periherals & Cables:         free self-powered USB 2.0 ports         Security slot         One cable with three connectors: Mini         Display Port with audio support, USB 2.0         AC power cord         Electrical & Operating Requirements:         Input voltage: 100V to 240V AC; 50-         60Hz         Including installation and commissioning				
Camera and microphone: Built-in insight with microphone Speakers: Built-in 2.1 speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: • Arsenic-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	1			
Built-in insight with microphone         Speakers: Built-in 2.1         speaker system (49 watts maximum)         Mini DisplayPort connector with audio         support         Environmental Status Report:         • Arsenic-free display glass         • BFR-free         • PVC-free 3         • Highly recyclable aluminum and glass enclosures         • Mercury-free LED-backlit display         Periherals & Cables:         free self-powered USB 2.0 ports         Security slot         One cable with three connectors: Mini         Display Port with audio support, USB 2.0         AC power cord         Electrical & Operating Requirements:         Input voltage: 100V to 240V AC; 50- 60Hz         Including installation and commissioning				
Speakers: Built-in 2.1         speaker system (49 watts maximum)         Mini DisplayPort connector with audio         support         Environmental Status Report:         • Arsenic-free display glass         • BFR-free         • PVC-free 3         • Highly recyclable aluminum         and glass enclosures         • Mercury-free LED-backlit display         Periherals & Cables:         free self-powered USB 2.0 ports         Security slot         One cable with three connectors: Mini         Display Port with audio support, USB 2.0         AC power cord         Electrical & Operating Requirements:         Input voltage: 100V to 240V AC; 50-         60Hz         Including installation and commissioning	-			
speaker system (49 watts maximum) Mini DisplayPort connector with audio support Environmental Status Report: • Arsenic-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	•			
Mini DisplayPort connector with audio         support         Environmental Status Report:         • Arsenic-free display glass         • BFR-free         • PVC-free 3         • Highly recyclable aluminum         and glass enclosures         • Mercury-free LED-backlit display         Periherals & Cables:         free self-powered USB 2.0 ports         Security slot         One cable with three connectors: Mini         Display Port with audio support, USB 2.0         AC power cord         Electrical & Operating Requirements:         Input voltage: 100V to 240V AC; 50-         60Hz         Including installation and commissioning	1			
support Environmental Status Report: • Arsenic-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	1			
Environmental Status Report: • Arsenic-free display glass • BFR-free • PVC-free 3 • Highly recyclable aluminum and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning				
<ul> <li>Arsenic-free display glass</li> <li>BFR-free</li> <li>PVC-free 3</li> <li>Highly recyclable aluminum and glass enclosures</li> <li>Mercury-free LED-backlit display</li> <li>Periherals &amp; Cables: free self-powered USB 2.0 ports</li> <li>Security slot</li> <li>One cable with three connectors: Mini</li> <li>Display Port with audio support, USB 2.0</li> <li>AC power cord</li> <li>Electrical &amp; Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz</li> <li>Including installation and commissioning</li> </ul>				
<ul> <li>BFR-free</li> <li>PVC-free 3</li> <li>Highly recyclable aluminum and glass enclosures</li> <li>Mercury-free LED-backlit display</li> <li>Periherals &amp; Cables: free self-powered USB 2.0 ports</li> <li>Security slot</li> <li>One cable with three connectors: Mini</li> <li>Display Port with audio support, USB 2.0</li> <li>AC power cord</li> <li>Electrical &amp; Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz</li> <li>Including installation and commissioning</li> </ul>	Environmental Status Report.			
<ul> <li>BFR-free</li> <li>PVC-free 3</li> <li>Highly recyclable aluminum and glass enclosures</li> <li>Mercury-free LED-backlit display</li> <li>Periherals &amp; Cables: free self-powered USB 2.0 ports</li> <li>Security slot</li> <li>One cable with three connectors: Mini</li> <li>Display Port with audio support, USB 2.0</li> <li>AC power cord</li> <li>Electrical &amp; Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz</li> <li>Including installation and commissioning</li> </ul>	• Arsenic-free display glass			
<ul> <li>PVC-free 3</li> <li>Highly recyclable aluminum and glass enclosures</li> <li>Mercury-free LED-backlit display</li> <li>Periherals &amp; Cables: free self-powered USB 2.0 ports</li> <li>Security slot</li> <li>One cable with three connectors: Mini</li> <li>Display Port with audio support, USB 2.0</li> <li>AC power cord</li> <li>Electrical &amp; Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz</li> <li>Including installation and commissioning</li> </ul>	1			
<ul> <li>Highly recyclable aluminum and glass enclosures</li> <li>Mercury-free LED-backlit display Periherals &amp; Cables: free self-powered USB 2.0 ports</li> <li>Security slot</li> <li>One cable with three connectors: Mini</li> <li>Display Port with audio support, USB 2.0</li> <li>AC power cord</li> <li>Electrical &amp; Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz</li> <li>Including installation and commissioning</li> </ul>				
and glass enclosures • Mercury-free LED-backlit display Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	• Highly recyclable aluminum			
Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning				
Periherals & Cables: free self-powered USB 2.0 ports Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	e			
Security slot One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	Periherals & Cables:			
One cable with three connectors: Mini Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	free self-powered USB 2.0 ports			
Display Port with audio support, USB 2.0 AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	Security slot			
AC power cord Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	One cable with three connectors: Mini			
Electrical & Operating Requirements: Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning				
Input voltage: 100V to 240V AC; 50- 60Hz Including installation and commissioning	•			
60Hz Including installation and commissioning				
Including installation and commissioning				
One Year Local Warranty	•			
	One Year Local Warranty			

#### E. Special Terms and conditions;

- i. Please submit the technical and financial bid (rates) on our prescribed BoQs Form and clearly mention the quoted model / brands as required in BoQs, with complete terms and conditions signed, stamped with both bids, otherwise your bid (s) may be rejected.
- ii. Bidders are requested to quote genuine / quality products without compromising on quality. The supplied products shall be inspected by our technical experts with respect to BoQs requirements and quality standards.
- iii. Purchase / work order (s) will be awarded on Item Wise Basis.
- iv. Kindly attach the Tender fee with Technical Bid and Bid money / CDR with Financial Bid.
- v. Multiple rates of an item may also lead to the rejection of bid / item.